# METAPLAST

## 10L (P2) Rectangular Tall Bucket

### **BUCKET FAMILY**

TYPE: RECTANGULAR BUCKET MODEL: MP GTRN 10000 PBW MP GTRN 10000 MBW MP GTRN 10000 MBC

Manufactured to BRC standards at a state-of-the-art production facility. Ideal for use with food, chemicals, animal feeds, horticulture and oils.

	/

### Features

Produced to BRC standards.
Tamper evidence.
Modern, clean design.
Colour variations from white/clear to order.
IML (in mould labels) options on most sizes.
Plastic/metal handle options on most sizes.
Applied with even numbers of bases and lids on each pallet.
Shipping from one palet to multi-pallet direct delivery.

Fully recyclable.

### 10L (P2) Rectangular Tall Bucket

Dimensions	Metric
Upper Length (inside)	286mm
Upper Width (with flange)	198,6mm
Upper Length (with handles)	249,3mm
Bottom Width (external)	161,1mm
Height (with standard lid)	266mm

Nominal Capacity	10 000ml
Total Capacity	11 700ml
Total Usable Capacity	10 600ml

Container weight	200~
Container weight	300g
Handle weight (PP)	16g
Handle weight (metal)	24g
Lid weight	57-59g

Weight tolerance	+/- 5%
Dimension tolerance	+/- 1mm

### **Raw Material / Transport and Warehousing**

Buckets and lids are made from food-grade polypropylene (PP).

Warehousing: sealed unit pallets, which include even numbers of bases and lids.

Filling and closing conditions: max. content temperature during filling 95°C. For stacking content temperature should be lower than 45°C. Put not more than 2 warm containers in the stack.

When outside temperature decreases to 25-30° containers will be more rigid and mechanical parameters allowing stacking for maximal static load as below.

Load on the lower container: Static (T<23°C) : < 45 kg Transparent containers < 36 kg

Palletizing of containers: product with density 1,6 g/cm3 according to the customer practice giving consideration to the mentioned earlier values.

All materials and dyes used to produce container or lid designed for the food sector are approved for food contact.

All packages from a single pallet should be used immediately after unpacking.

Manufacturer is not responsible for container deformation if stacked with other products on top of finished pallet.

### Pelletisation at delivery

480 units (buckets & lids) per pallet

### **Standard Colours**



Colour and IML options available (minimum orders apply).

### **Metaplast Ltd**

Unit A1, Ground Floor, Meridian House Meridian Business Park, Norwich NR7 0TA Tel: +44 (0)1508 495342 sales@metaplast.co.uk www. metaplast.co.uk

While every care has been taken to ensure that product specifications are accurate, they are given for guidance only. For uses where specification is critical, customers are advised to check with Metaplast prior to purchase. We reserve the right to amend product specifications without prior notice.