

2.75L Round Bucket

BUCKET FAMILY

TYPE: ROUND BUCKET MODEL: MP GTLF 2750 PBW MP GTLF 2750 PBC

Manufactured to BRC standards at a state-of-the-art production facility. Ideal for use with food, chemicals, animal feeds, horticulture and oils.

_							
	0	-			22	0	-
	c	а	u	ч		c	-

Produced to BRC standards.	
Tamper evidence.	
Modern, clean design.	
Colour variations from white/clear to order.	
IML (in mould labels) options on most sizes.	
Plastic/metal handle options on most sizes.	
Applied with even numbers of bases and lids on each pallet.	
Shipping from one palet to multi-pallet direct delivery.	

Fully recyclable.



2.75L Round Bucket

Dimensions	Metric		
Upper Diameter (inside)	162,8mm		
Upper Diameter (with flange)	174mm		
Upper Diameter (with handles)	173,2mm		
Bottom Diameter (external)	144,5mm		
Height (with standard lid)	154,4mm		
Height (with lid for foiling)	-		
Nominal Capacity	2500ml		
Total Capacity	2800ml		
Total Usable Capacity	2600ml		

Container weight with handle	76,3g
Handle weight (strap)	2,9g
Handle weight (PP)	-
Handle weight (metal)	12g
Lid weight	17,5g
Weight tolerance	+/- 5%
Dimension tolerance	+/- 1mm

Raw Material / Transport and Warehousing

Buckets and lids are made from food-grade polypropylene (PP).

Warehousing: sealed unit pallets, which include even numbers of bases and lids.

Filling and closing conditions: max. content temperature during filling 95°C. For stacking content temperature should be lower than 45°C. Put not more than 2 warm containers in the stack.

When outside temperature decreases to 25-30° containers will be more rigid and mechanical parameters allowing stacking for maximal static load as below.

Load on the lower container: Static (T<23°C) : < 25 kg Transparent containers < 20 kg

Palletising of containers: product with density 1,6 g/cm3 according to the customer practice giving consideration to the mentioned earlier values.

All materials and dyes used to produce container or lid designed for the food sector are approved for food contact.

All packages from a single pallet should be used immediately after unpacking.

Manufacturer is not responsible for container deformation if stacked with other products on top of finished pallet.

Palletisation at delivery

2220 units/pallet packaging: carton box

Standard Colours



Colour and IML options available (minimum orders apply).

Metaplast Ltd

Unit A1, Ground Floor, Meridian House Meridian Business Park, Norwich NR7 0TA Tel: +44 (0)1508 495342 sales@metaplast.co.uk

www. metaplast.co.uk

While every care has been taken to ensure that product specifications are accurate, they are given for guidance only. For uses where specification is critical, customers are advised to check with Metaplast prior to purchase. We reserve the right to amend product specifications without prior notice.